
## ST. CLAIR RIVER


MC FILE CORY Aerial Drogue Survey Surface Velocities and Directions

Spring of 1982

600 AD-A202







Boyorgra acoil and them a entra store drana and solo; its



US Army Corps of Engineers

September 1983

**Detroit District** 

Great Lakes Hydraulics and Hydrology Branch

082 29 12

REPORT DOCUMENTATION PAGE					Form Approved OMB No. 0704-0188	
1a. REPORT SECURITY CLASSIFICATION Unclassified		16. RESTRICTIVE MARKINGS				
2a. SECURITY CLASSIFICATION AUTHORITY		3. DISTRIBUTION/AVAILABILITY OF REPORT				
2b. DECLASSIFICATION / DOWNGRADING SCHEDULE		Approved for public release;				
4. PERFORMING ORGANIZATION REPORT NUMBER(S)		distribution unlimited  5. MONITORING ORGANIZATION REPORT NUMBER(S)				
60. NAME OF PERFORMING ORGANIZATION	6b. OFFICE SYMBOL (If applicable)	78. NAME OF MONITORING ORGANIZATION				
U.S. Army Engineer						
District, Detroit 6c ADDRESS (City, State, and ZIP Code)	CENCE-ED-L	7b. ADDRESS (City, State, and ZIP Code)				
Detroit District		, , , , , , , , , , , , , , , , , , , ,				
P.O. Box 1027		1				
Detroit. MI 48231  Ba. NAME OF FUNDING/SPONSORING TAB. OFFICE SYMBOL		9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER				
ORGANIZATION U.S. Army	(If applicable)	2. VIOCONEWENT INSTRUMENT IDENTIFICATION NO.				
Corps of Engineers c ADDRESS (City, State, and ZIP Code)		10 SOURCE OF EUNIONIC MUMBERS				
Detroit District		10. SOURCE OF FUNDING NUMBERS PROGRAM PROJECT TASK WORK UNIT				
P.O. Box 1027		ELEMENT NO.	NO.	NO.	ACCESSION NO.	
Detroit. MI 48231 11. TITLE (Include Security Classification)		<u></u>	<u> </u>			
St. Clair River - Aerial Drogue Survey, Surface Velocities and Direction,						
Spring of 1982		<u> </u>				
12. PERSONAL AUTHOR(S)	1 ** 1 1 . *					
Great Lakes Hydraulics an 13a. TYPE OF REPORT 13b. TIME C	OVERED	14. DATE OF REPO	RT (Year, Month	Day) 15. F	PAGE COUNT	
Final FROM	TO		mber 1983		39	
16. SUPPLEMENTARY NOTATION						
17. COSATI CODES	18. SUBJECT TERMS (	Continue on revers	e if necessary an	d identify by	block number)	
FIELD GROUP SUB-GROUP	Water Surf	face Currents, St. Clair River,				
		Merial Time-Lapse Photography,				
19. ABSTRACT (Continue on reverse if necessary	Flow Patte					
the state of the s						
This report presents the results of a St. Clair River open water surface						
current study and briefly describes the procedures used. The collection						
of data involved tracking of drogues via aerial time-lapse photography along the entire St. Clair River. The report contains drogue charts						
displaying drogue tracking through the major channels of the St. Clair						
River. The data enables the user to quickly assess the flow pattern of						
the river at various locations, thus allowing prediction of the movement						
and behavior of possible pollutants so counter measures can be taken.						
They are also useful to navigational interests, both commercial and						
recreational, as well as aiding in search and rescue operations of the						
Coast Guard.						
20. DISTRIBUTION/AVAILABILITY OF ABSTRACT	M. Demonder	21. ABSTRACT SECURITY CLASSIFICATION UD.C.I. a. B. E. I. T. I. e. d.				
■ UNCLASSIFIED/UNLIMITED ■ SAME AS I	PT. DTIC USERS	225 TELEPHONE (313) 22			CE SAWBOF	
Thomas Freitag	Provious aditions are				CB-PD-BA	

A STATE OF THE STA

Y

CONTRACTOR OF THE PROPERTY OF

#### ST. CLAIR RIVER

### AERIAL DROGUE SURVEY SURFACE VELOCITIES AND DIRECTIONS

SPRING OF 1982


BY

U.S. ARMY CORPS OF ENGINEERS
DETROIT DISTRICT

GREAT LAKES HYDRAULICS AND HYDRO: OGY BRANCH

SEPTEMBER 1983

This document has been approved for public release and sale; its distribution is unlimited.



Special

Dist

#### ST. CLAIR RIVER AERIAL DROGUE SURVEY SPRING OF 1982

#### TABLE OF CONTENTS

TAGE	- NO:
INTRODUCTION	. 1
PURPOSE AND SCOPE	. 1
STUDY AREA DESCRIPTION	. 1
FIELD PROGRAM	,2
ESTABLISHMENT OF SURVEY REACHES	.2
DATA ACQUISITION	.2
DATA REDUCTION	,4
RESULTS AND ANALYSIS	,4
CONCLUSIONS	.5
LIST OF FIGURES	
FIGURE PAGI	NO.
1. TYPICAL AERIAL DROGUE	.3
2. WIND GRAPH	.6
3. ST. CLAIR RIVER INDEX CHART	.7
INCLOSURE - DROGUE CHARTSSHEETS 1-2	29

#### ST. CLAIR RIVER ABRIAL DROGUE SURVEY SPRING OF 1982

#### INTRODUCTION

The mission of the Great Lakes Hydraulics and Hydrology Branch of the Detroit District Corps of Engineers' Engineering Division includes the collection and analysis of technical data related to the movement of waters of the Great Lakes. As such, the branch was requested to collect and analyze surface current data (directionals and velocities) under open water conditions for the St. Clair River. These data are useful to a number of interests including: the Coast Guard, to determine the probable areas that would be impacted by an oil or toxic substance spill under varying flow and meteorological conditions; local communities and engineers, in the design of sewer outfall and water intake; those involved in pollution studies and design of dredge disposal sites; and both commercial and recreational navigation interests.

#### PURPOSE AND SCOPE

The purpose of this report is to present the results of a St. Clair River open water surface current study and to briefly describe the procedures utilized in this undertaking. The collection of data was conducted in May and June 1982 and involved the tracking of drogues via aerial time-lapse photography along the entire river.

#### STUDY AREA DESCRIPTION

The St. Clair River has three distinct reaches. The upper reach, extending downstream from Lake Huron to a point about three miles below the Blue Water Bridge, is approximately 800 feet wide at its narrowest point and has mid-channel depths varying from 30 to 70 feet. Maximum velocities in this reach occur near the Blue Water Bridge. The middle reach, which extends downriver for the next 27 miles, is approximately one-half mile wide, with channel depths ranging from 27 to 50 feet. Located in this reach are Fawn Island, Stag Island and a middle ground shoal opposite the City of St. Clair, Michigan. The lower reach continues downstream for the next nine miles to Lake St. Clair, where it divides into a number of channels which flow across a delta called the St. Clair Flats. Average velocities in the St. Clair River range from two to six feet per second, depending upon the reach and controlling characteristics.

#### FIELD PROGRAM

#### ESTABLISHMENT OF SURVEY REACHES

Prior to the start of the drogue survey, the entire St. Clair River was divided into nine survey reaches, varying in length from 2 to 24 miles. To insure uniform coverage of the river system as the job progressed, additional subdivisions of these nine reaches were made at the discretion of the survey crew. These further partitions left the original number of survey reaches unchanged. Sufficient horizontal control was accomplished through a constraint that at least one, and preferably both, of the shorelines appear in aerial photographs. Vertical control information was provided by the existing water level gage network on the St. Clair River.


#### DATA ACQUISITION

A 35-foot survey launch, the "Korkigian", and a 21-foot "MonArk" trihull were used to deploy drogues at the upstream end of the respective survey reaches. An airplane was used to take aerial time-lapse photographs. The Drogues, 4'x4' pieces of plywood, have a line down to a weighted vane, painted white for visibility and individually numbered for identification (See Figure 1), were released at equal intervals across the river. After deployment, the boat crew either followed or preceded the drogues until the photographic crew asked for a reset or pick up of the targets (drogues). This method allowed for the servicing of those drogues which ran aground in shoal areas or were upended by passing vessels and insured that any crossover between the drogue paths would be quickly detected and recorded.

The photographic operations involved repeated passes of an airplane over each of the reaches until the track of the drogues over an entire reach was captured in aerial photos. Timing was such that the maximum distance traveled by the drogues between passes would not exceed 2,000 feet. The typical photo scale employed was 1:9960 with a standard 60% overlap between photos.

Coordination between the airplane's photographic crew and the boat's crew was maintained by radio. For accurate data, minimal cloud cover at the preselected flight altitude was needed. This insured adequate light for drogue identification, while still maintaining sufficient shoreline configuration coverage for control purposes. Other constraints included releasing the drogues only when the surface waves were below 0.5 feet in height and near surface winds were less than 10 miles per hour.

# TYPICAL AERIAL DROGUE



#### DATA REDUCTION

Drogue positions were scaled from the individual photos and were accurately plotted on drogue charts. The positions deduced from each exposure, combined with the recorded time to the nearest second, gave the path and velocity of each target as it floated downstream. As a final product, these data were transferred onto wash-off mylar sheets. The scale chosen for the drogue charts was 1:10,000.

#### RESULTS AND ANALYSIS

Drogue tracking, through the major channels of the St. Clair River, is displayed on drogue charts (see sheets 1-29). Velocities are depicted in units of feet per second, along with their associated vectors. Vector lengths on the 1:10,000 scale drogue charts are such that 0.10 inch corresponds to one foot per second of velocity. All vectors are portrayed in the direction of the plotted surface flow. An index chart, divided into twenty-nine sectors each of which represents a given drogue chart, is also attached and can be found directly after Figure 2 (Wind Graph). Sectors proceed downstream from the Blue Water Bridge to the delta of the river.


Average flow in the St. Clair River, from river gage calculations, during the period of study (May-June 1982) was 189,000 cubic feet per second (cfs) and all of the plotted velocities are based on this flow. Any deviation from the 189,000 cfs flow can be assumed to yield a corresponding deviation from the plotted velocities; i.e., a 10% flow change would account for a 10% velocity change for any given point on the river. This is a simplification of the actual velocity change due to variations in flow and should be considered as an approximate value.

Wind conditions during this study were less than 10 miles per hour and wave heights were less than one foot. Changes in wind direction and velocity will effect the flow patterns shown in this study. In the event of an oil or toxic substance spill, wind patterns of the study area should be seriously considered. For that purpose a wind graph has been imposed on the drogue charts, sheets 1-29. The wind graph for this study uses the 16 principal points of the compass showing the relative frequency and strength of winds from these directions. The wind speed and direction observations used for this graph were recorded at the Detroit, Michigan, City Airport. For interpretation of the wind graph see Figure 2.

#### CONCLUSIONS


This study provides useful surface current data needed by many St. Clair River interests. These data are presented as vectors that indicate velocity and direction on charts of the St. Clair River system. Also presented is a wind graph. The data enables the user to quickly assess the flow pattern of the river at various locations; and thus will allow for prediction of the movement and behavior of possible pollutants so countermeasures can be enacted. These data are also useful to navigational interests, both commercial and recreational, as well as aiding in search and rescue operations of the Coast Guard.

## WIND GRAPH (Detroit, Michigan City Airport)




All ceiling and visibility conditions

Figure 2




ら、後後


CONF. T. A. N. S. ARMINER OF W. C. SALANDER STREET




SCALE 1

1






SCALE




SCALE 1 : 10,000


SHEET NO. 2





ţ


SCALE




















SHEET NO. 6








SHEET NO. 7





Commence of the Commence of th





















The state of the







SHEET NO. 12










SCALE ( : )







1








SCALE






































SCAL









## LEGGE


VELOCITY IN PEET PER SECONS


MINATES SHOOL AREA


SCALE 1:10,000

















SCALE 1:10,000

----







SCALE I

